

Printing date 02.06.2015 Version number 100 Revision: 02.06.2015

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black
- · Article number: 04003 / 04007 / 04008 / 04010 / 04018 /04019 02000 (Silver 150 ml)
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

- · Further information obtainable from: QHSE Department
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h 17:00h)

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



H319 Eye Irrit. 2 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xi; Irritant

R36: Irritating to eyes.

GHS07



F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurised container.

Has a narcotising effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Printing date 02.06.2015 Version number 100 Revision: 02.06.2015

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

(Contd. of page 1)

#### · 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

#### · Signal word Danger

### · Hazard-determining components of labelling:

acetone

n-butyl acetate

butan-1-ol

propan-2-ol

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

*P251* Do not pierce or burn, even after use.

*P211* Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

#### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

| · Dangerous components:   |   |          |
|---|---|----------|
| CAS: 67-64-1<br>EINECS: 200-662-2<br>Index number: 606-001-00-8 | acetone  Xi R36  F R11  | 25-50%   |
| Reg.nr.: 01-2119471330-49-xxxx                                  | R66-67  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336 |          |
| CAS: 123-86-4<br>EINECS: 204-658-1                              | n-butyl acetate<br>R10-66-67                                    | 10-12.5% |
| Index number: 607-025-00-1<br>Reg.nr.: 01-2119485493-29-xxxx    | ·   | .1. 2    |

(Contd. on page 3)

 Printing date 02.06.2015
 Version number 100
 Revision: 02.06.2015

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

|  | · ·   | ontd. of page |
|--|---|---------------|
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5                                    | propane<br>F+ R12<br>Flam. Gas 1, H220  | 10-12.5%      |
| Reg.nr.: 01-2119486944-21-xxxx   | Press. Gas C, H280  |               |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Index number: 607-195-00-7<br>Reg.nr.: 01-2119475791-29-xxxx | 2-methoxy-1-methylethyl acetate<br>R10  | 5-10%         |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119474691-32-xxxx | butane F+ R12 Flam. Gas 1, H220 Press. Gas C, H280  | 5-10%         |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119485395-27-xxxx  | isobutane  F+ R12  F + R12  Flam. Gas 1, H220  Press. Gas C, H280   | 5-10%         |
| CAS: 71-36-3<br>EINECS: 200-751-6<br>Index number: 603-004-00-6<br>Reg.nr.: 01-2119484630-38-xxxx  | butan-1-ol  Xn R22  Xi R37/38-41  R10-67  Flam. Liq. 3, H226  Eye Dam. 1, H318  ↑ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 2.5-5%        |
| CAS: 9004-70-0   | Nitrocellulose (nitrogen content <12.6%)  F R11  Flam. Sol. 1, H228   | 2.5-5%        |
| CAS: 67-63-0<br>EINECS: 200-661-7<br>Index number: 603-117-00-0<br>Reg.nr.: 01-2119457558-25-xxxx  | propan-2-ol  Xi R36  F R11  R67  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336  | 1-2.5%        |

· Additional information: For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 4)

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

(Contd. of page 3)

· 5.3 Advice for firefighters

· Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

| · Ingredients with limit values th | it require monitoring | at the workplace: |
|------------------------------------|-----------------------|-------------------|
|------------------------------------|-----------------------|-------------------|

#### 67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

#### 123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

(Contd. on page 5)

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Protection of hands: Not required.
- · Material of gloves Not required.
- Penetration time of glove material Not required.
- · Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

*Melting point/Melting range:* Undetermined.

**Boiling point/Boiling range:** Not applicable, as aerosol.

• Flash point:  $< 0 \, ^{\circ}C \, (< 32 \, ^{\circ}F)$ 

Not applicable, as aerosol.

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 333 °C (631 °F)

· Decomposition temperature: Not determined.

· Self-igniting: Product is not selfigniting.

(Contd. on page 6)

 Printing date 02.06.2015
 Version number 100
 Revision: 02.06.2015

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

|                                       | (Contd. of  |
|---------------------------------------|---|
| Danger of explosion:                  | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits:                     |   |
| Lower:                                | 1.2 Vol %   |
| Upper:                                | 13.0 Vol %  |
| Vapour pressure at 20 °C (68 °F):     | 3500 hPa (2625 mm Hg)   |
| Density at 20 °C (68 °F):             | 0.766 g/cm³ (6.392 lbs/gal)   |
| Relative density                      | Not determined.   |
| Vapour density                        | Not determined.   |
| Evaporation rate                      | Not applicable.   |
| Solubility in / Miscibility with      |   |
| water:                                | Not miscible or difficult to mix.   |
| Partition coefficient (n-octanol/wate | r): Not determined.   |
| Viscosity:                            |   |
| Dynamic:                              | Not determined.   |
| Kinematic:                            | Not determined.   |
| Solvent content:                      |   |
| Organic solvents:                     | 87.9 %  |
| EU-VOC:                               | 673.5 g/l   |
| EU-VOC in %:                          | 87.92 %   |
| Solids content:                       | 3.0 %   |
| 9.2 Other information                 | No further relevant information available.  |

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

| 67-64-1 ac | etone         |                       |                |
|------------|---------------|-----------------------|----------------|
| Oral       | LD50          | 5800 mg/kg (rat)      |                |
| Dermal     | <i>LD50</i>   | 20000 mg/kg (rabbit)  |                |
| Inhalative | LC50 / 4 h    | 39 mg/m3 (rat)        |                |
| 123-86-4 n | i-butyl aceta | nte                   |                |
| Oral       | LD50          | 10770 mg/kg (rat)     |                |
| Dermal     | <i>LD50</i>   | >17600 mg/kg (rabbit) |                |
| Inhalative | LC50 / 4 h    | >21.0 mg/m3 (rat)     |                |
| 108-65-6 2 | -methoxy-1    | -methylethyl acetate  |                |
| Oral       | LD50          | 8532 mg/kg (rat)      |                |
|            | •             |                       | (Contd. on pag |

- GB

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

|            |            | (Contd. of page 6)   |
|------------|------------|----------------------|
| Dermal     | LD50       | >5000 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | 35.7 mg/m3 (rat)     |
| 106-97-8 b | utane      |                      |
| Inhalative | LC50 / 4 h | 658000 mg/m3 (rat)   |
| 71-36-3 bu | tan-1-ol   |                      |
| Oral       | LD50       | 2292 mg/kg (rat)     |
| Dermal     | LD50       | 3430 mg/kg (rabbit)  |
| Inhalative | LC50 / 4 h | 17.76 mg/m3 (rat)    |
| 67-63-0 pr | opan-2-ol  |                      |
| Oral       | LD50       | 5045 mg/kg (rat)     |
| Dermal     | LD50       | 12800 mg/kg (rabbit) |
|            | LC50/4 h   | 30 mg/m3 (rat)       |

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

# SECTION 12: Ecological information

· 12.1 Toxicity

| · Aquatic toxicity:  |                                 |
|----------------------|---------------------------------|
| 67-64-1 acetone      |                                 |
| EC50 / 48 h          | 8800 mg/l (daphnia magna)       |
| LC50 / 48 h          | 2262 mg/l (daphnia magna)       |
| LC50 / 96 h (static) | 5540 mg/l (fish)                |
| 123-86-4 n-butyl ace | tate                            |
| EC50 / 48 h          | 44 mg/l (daphnia magna)         |
| EC50 / 96 h          | 320 mg/l (algae)                |
| LC50 / 24 h          | 205 mg/l (daphnia magna)        |
| LC50 / 96 h          | 18 mg/l (Pimephales promelas)   |
| 108-65-6 2-methoxy-  | 1-methylethyl acetate           |
| EC50                 | 408 mg/l (daphnia magna)        |
| 71-36-3 butan-1-ol   |                                 |
| EC50 / 48 h          | 1328 mg/l (daphnia magna)       |
| EC50 / 72 h          | 8500 mg/l (algae)               |
| LC50 / 96 h          | 1376 mg/l (Pimephales promelas) |
| 67-63-0 propan-2-ol  | •                               |
| EC50 / 48 h          | 13299 mg/l (daphnia magna)      |
| LC50/96 h (dynamic   | 4200  mg/l (fish)               |

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

(Contd. of page 7)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European | waste catalogue   |
|------------|---|
| 08 01 11*  | waste paint and varnish containing organic solvents or other dangerous substances |
| 15 01 04   | metallic packaging  |

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

| 14.1 UN-Number                    |                     |  |
|-----------------------------------|---------------------|--|
| ADR, IMDG, IATA                   | UN1950              |  |
| 14.2 UN proper shipping name      |                     |  |
| ADR                               | 1950 AEROSOLS       |  |
| IMDG                              | AEROSOLS            |  |
| IATA                              | AEROSOLS, flammable |  |
| 14.3 Transport hazard class(es)   |                     |  |
| ADR                               |                     |  |
| **                                |                     |  |
| Class                             | 2 5F Gases.         |  |
| Label                             | 2.1                 |  |
| IMDG, IATA                        |                     |  |
| Class                             | 2.1                 |  |
| Label                             | 2.1                 |  |
| 14.4 Packing group                |                     |  |
| ADR, IMDĞ, İATA                   | Void                |  |
| 14.5 Environmental hazards:       |                     |  |
| Marine pollutant:                 | No                  |  |
| 14.6 Special precautions for user | Warning: Gases.     |  |
| Danger code (Kemler):             | -                   |  |

onta. on page 2

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

|  | (Contd. of                         | f page |
|--|------------------------------------|--------|
| · EMS Number:                                  | F-D,S-U                            |        |
| · 14.7 Transport in bulk according to Anne     | ex II of                           |        |
| MARPOL73/78 and the IBC Code                   | Not applicable.                    |        |
| · Transport/Additional information:            |                                    |        |
| $\cdot ADR$                                    |                                    |        |
| · Limited quantities (LQ)                      | IL                                 |        |
| · Excepted quantities (EQ)                     | Code: E0                           |        |
|  | Not permitted as Excepted Quantity |        |
| · Transport category                           | 2                                  |        |
| · Tunnel restriction code                      | D                                  |        |
| · IMDG   |                                    |        |
| · Limited quantities (LQ)                      | 1L                                 |        |
| $\cdot$ Excepted quantities $(\widetilde{EQ})$ | Code: E0                           |        |
|  | Not permitted as Excepted Quantity |        |
| · UN ''Model Regulation'':                     | UN1950, AEROSOLS, 2.1              |        |

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R37/38 Irritating to respiratory system and skin.
- R41 Risk of serious damage to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: R&D legislation and regulatory advisor
- · Contact: Mr. K. Smedeman

(Contd. on page 10)

Version number 100 Printing date 02.06.2015 Revision: 02.06.2015

Trade name: MOTIP WHEEL SPRAY White / Silver / Gold / Steel Wheel / Black

(Contd. of page 9)

#### · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3 Flam. Sol. 1: Flammable solids, Hazard Category 1

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

\* \* Data compared to the previous version altered.